

# Safety Data Sheet according to Regulation (EC)

## No. 1907/2006 (REACH)

Printed 30.11.2010  
Revision 30.11.2010 (GB) Version 8.1

### R 1270 (Propene)

0068

## 1. Identification of the substance/mixture and of the company/undertaking

### Product identifier

**Name of product** R 1270 (Propene)  
Art-Nr.: 0068  
**Name of substance** propene  
**Index No** 601-011-00-9  
**EC No** 204-062-1  
**CAS No** 115-07-1

### Manufacturer/distributor

GHC Gerling, Holz & Co. Handels GmbH  
Ruhrstraße 113, D-22761 Hamburg  
Phone +49 (0) 40 853 123-0, Fax +49 (0) 40 853 123-66

E-Mail [msds@ghc.de](mailto:msds@ghc.de)  
Internet [www.ghc.de](http://www.ghc.de)

### Advice

Phone +49 (0) 40 853 123-0  
Fax +49 (0) 40 853 123-66

### Emergency advice

GHC Gerling, Holz & Co. Handels GmbH  
Phone +49 (0) 40 853 123-0

### Recommended intended purpose(s)

Refrigerant.

## ! 2. Hazards identification

### Classification according to 67/548/EEC or 1999/45/EC

F+; R12

### R-phrases

12 Extremely flammable.

### Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

<b>Flam. Gas 1</b>	<b>H220</b>
--------------------	-------------

<b>Liquef. Gas</b>	<b>H280</b>
--------------------	-------------

### Hazard statements for physical hazards

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

### Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS02



GHS04

## Safety Data Sheet according to Regulation (EC)

### No. 1907/2006 (REACH)

Printed 30.11.2010  
Revision 30.11.2010 (GB) Version 8.1

### R 1270 (Propene)

0068

#### Signal word

Danger

#### Hazard statements for physical hazards

H220 Extremely flammable gas.  
H280 Contains gas under pressure; may explode if heated.

#### Precautionary Statements

##### Prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

##### Response

P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.  
P381 Eliminate all ignition sources if safe to do so.

##### Storage

P403 Store in a well-ventilated place.

#### Hazardous ingredients for labeling

propene

#### ! Information pertaining to special dangers for human and environment

In high concentrations may cause asphyxiation.  
Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.  
Contact with liquid may cause cold burns/frostbite.

### ! 3. Composition/information on ingredients

CAS No 115-07-1 propene  
EC No 204-062-1  
Index No 601-011-00-9

### ! 4. First aid measures

#### General information

Remove contaminated soaked clothing immediately.  
Adhere to personal protective measures when giving first aid.  
Seek medical advice immediately.

#### In case of inhalation

Remove the casualty into fresh air and keep him immobile.  
Seek medical treatment immediately.  
In case of respiratory standstill give artificial respiration by respiratory bag (Ambu bag) or respirator. Send for a doctor.

#### In case of skin contact

In case of contact with skin wash off with warm water.  
In case of frostbite rinse with plenty of water. Don't remove clothing.  
In case of frostbite spray with lukewarm (not hot) water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.

#### ! In case of eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Call for a doctor immediately.

#### In case of ingestion

Ingestion is not considered a potential route of exposure.

#### Physician's information / possible symptoms

Shortness of breath

#### Treatment (Advice to doctor)

Monitor circulation.

## Safety Data Sheet according to Regulation (EC)

### No. 1907/2006 (REACH)

Printed 30.11.2010

Revision 30.11.2010 (GB) Version 8.1

### R 1270 (Propene)

0068

---

## 5. Firefighting measures

### Suitable extinguishing media

Dry powder  
Carbon dioxide

### Extinguishing media which must not be used for safety reasons

no

### Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

Formation of explosive gas mixtures in air.

In the event of fire the following can be released:

Carbon monoxide (CO)

### Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply ( isolated ).

Wear full protective clothing.

### Additional information

Cool endangered containers with water spray jet.

Exposure to fire may cause containers to rupture/explode.

Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur.

Extinguish any other fire.

---

## 6. Accidental release measures

### Personal precautions

See chapter 8.

Keep away sources of ignition.

### Environmental precautions

If possible, stop flow of product.

Eliminate ignition sources.

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

### Methods for cleaning up

Ensure adequate air ventilation.

Allow to vaporise.

### Additional Information

Informations for safe handling see chapter 7.

Informations for personal protective equipment see chapter 8.

---

## ! 7. Handling and storage

### ! Advice on safe handling

Use only in thoroughly ventilated areas.

Transfer and handle only in enclosed systems.

Take measures against electrostatically charging.

Barrels and installations thoroughly earthing (grounding ).

Use antistatic tools.

Treatment only in suitable rooms and systems.

Provide good room ventilation even at ground level (vapours are heavier than air).

Prevent cylinders from falling over.

Ensure valve protection device is correctly fitted.

Ensure valve outlet cap nut or plug (where provided) is correctly fitted.

Open valve slowly to avoid pressure shock.

Do not allow backfeed into the container.

Suck back of water into the container must be prevented.

## Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 30.11.2010

Revision 30.11.2010 (GB) Version 8.1

R 1270 (Propene)

0068



No water to valves, flanges and other fittings.  
Purging of pipes and valves with inert gases - to avoid: water, solvents.

### Advice on protection against fire and explosion

The product is combustible.  
Because of risk of explosion avoid vapours getting into cellar, sewage system and holes.  
Take precautionary measures against static discharges.  
Formation of explosive gas mixtures in air.  
Use explosion-proof equipment / fittings and non-sparking tools.

### Requirements for storage rooms and vessels

Keep in closed original container.  
Ventilate store-rooms thoroughly.  
Use transportable pressure equipment.  
Suitable materials: Normalised steel and carbon steel, tempered steel, aluminium alloys, stainless steel.  
Valve: Suitable materials: Brass, copper alloys, carbon steels, aluminium alloys, stainless steel.

### Advice on storage compatibility

Do not store together with animal feedstuffs.  
Do not store together with food.  
Do not store together with oxidizing agents.

### Further information on storage conditions

Ensure valve protection device is correctly fitted.  
Keep container tightly closed and store at cool and aired place.  
Prevent cylinders from falling over.  
Keep container in a well-ventilated place  
Protect of heat.  
Storage temperature may not exceed 50°C (=122°F).

### Information on storage stability

At appropriate storage unlimited stability.

### Recommendation(s) for intended use

no

## 8. Exposure controls/personal protection

### Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
115-07-1	Propylene	TLV, 8 hours		500	ACGIH, USA

### Additional advice

no

### Respiratory protection

Keep self contained breathing apparatus readily available for emergency use.  
In case of rescue and maintenance activities in storage containers use environment-independent breathing apparatus because of risk of suffocation by edging out of air oxygen

### Hand protection

chemical-resistant gloves  
Leather gloves

### Eye protection

safety goggles, in case of increased risk add protective face shield

### Skin protection

antistatic boots

### General protective measures

Do not inhale gases/vapours/aerosols.

**Safety Data Sheet according to Regulation (EC)****No. 1907/2006 (REACH)**

Printed 30.11.2010

Revision 30.11.2010 (GB) Version 8.1

**R 1270 (Propene)**

0068

**Hygiene measures**

At work do not eat, drink and smoke.

**Limitation and surveillance of the environment**

See chapter 7.

**9. Physical and chemical properties****Form**

Gaseous / liquefied under pressure.

**Colour**

colourless

**Odour**

sweetish

**Important health, safety and environmental information**

	Value	Temperature	at	Method	Remark
<b>pH value in delivery state</b>	not applicable				
<b>Acid number</b>	not applicable				
<b>boiling point</b>	-47,7 °C		1013 hPa		
<b>melting point</b>	-185,3 °C				
<b>Flash point</b>	-108 °C				
<b>Flammable solid</b>	not applicable				
<b>Ignition temperature</b>	460 °C			DIN 51794	
<b>Lower explosion limit</b>	2,4 Vol-%				
<b>Upper explosion limit</b>	10,3 Vol-%				
<b>Vapour pressure</b>	10160 hPa	20 °C			
<b>Density</b>	0,521 g/cm <sup>3</sup>	20 °C			liquid phase
<b>Rel. vapour density</b>	1,48				air = 1
<b>Solubility in water</b>	200 mg/l	25 °C			
<b>Solubility/other</b>					soluble in organic solvent
<b>Partition coefficient (log p<sub>OW</sub>)</b>	1,77				
<b>Viscosity dynamic</b>	0,0943 mPa*s	20 °C			liquid phase

**Additional information**

Vapours are heavier than air.

# Safety Data Sheet according to Regulation (EC)

## No. 1907/2006 (REACH)

Printed 30.11.2010

Revision 30.11.2010 (GB) Version 8.1

### R 1270 (Propene)

0068

## 10. Stability and reactivity

### Conditions to avoid

Formation of explosive gas/air mixtures.

Heat sources / heat - risk of bursting.

### Materials to avoid

Reactions with oxidising agents.

### Hazardous decomposition products

Carbon monoxide

### Thermal decomposition

Remark No decomposition if used as directed.

### Additional information

Stable under normal conditions.

## 11. Toxicological information

### Acute toxicity/Irritability/Sensitization

	Value/Validation	Species	Method	Remark
<b>LC50 acute inhalation</b>	658 mg/l (4 h)	rat		
<b>Irritability skin</b>		no		
<b>Irritability eye</b>		no		
<b>Skin sensitization</b>		not determined		
<b>Sensitization respiratory system</b>		not determined		

### Subacute Toxicity - Carcinogenicity

	Value	Species	Method	Validation
<b>Mutagenicity</b>				Information on genotoxicity in vivo available.
<b>Reproduction-Toxicity</b>				not determined
<b>Carcinogenicity</b>				Data insufficient.

### Toxicity test (Additional information)

No experimental indication of genotoxicity in vitro ( Ames-test negative ).

### Experiences made from practice

May cause frostbite.

Gases have a suffocating effect.

Inhalation causes narcotic effect/intoxication.

## Safety Data Sheet according to Regulation (EC)

### No. 1907/2006 (REACH)

Printed 30.11.2010

Revision 30.11.2010 (GB) Version 8.1

### R 1270 (Propene)

0068



## 12. Ecological information

### Data on elimination (persistence and degradability)

	Elimination rate	Method of analysis	Method	Validation
<b>Physico-chemical degradability</b>	At normal temperature very highly volatile or gaseous product that can be released to atmosphere. Elimination test cannot be employed.			

**Biological eliminability** not determined

### Mobility and bioaccumulative potential

Because of the n-octanol/water distribution coefficient (log K<sub>ow</sub>) accumulation in organisms is possible.

### Ecotoxicological effects

	Value	Species	Method	Validation
<b>Fish</b>	not determined			
<b>Daphnia</b>	not determined			
<b>Algae</b>	not determined			
<b>Bacteria</b>	not determined			

## 13. Disposal considerations

### Waste code No.

16 05 04\*

### Name of waste

gases in pressure containers (including halons) containing dangerous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 91/689/EEC on hazardous waste.

### Recommendations for the product

Dispose of as hazardous waste.

### Recommendations for packaging

Transportable pressure equipment (empty, residual pressure): Return to supplier / manufacturer.

## 14. Transport information

### Land and inland navigation transport ADR/RID

UN 1077 PROPYLENE, 2.1, (B/D), Classification code: 2F

### Marine transport IMDG

UN 1077 PROPYLENE, 2.1

Ems: F-C, S-U

### Air transport ICAO/IATA-DGR

UN 1077 Propylene, 2.1

