

**R 32**

Print date 05.10.2022  
Revision date 05.10.2022  
Version 5.0 (en)  
replaces version of 14.07.2020 (4.0)

**\* SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

**Trade name/designation** R 32  
**Art-Nr(n).** 0032  
**Substance name** Difluoromethane (R 32)  
**EC No.** 200-839-4  
**REACH No.** 01-2119471312-47  
**CAS No.** 75-10-5

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

**Use of the substance/mixture**  
Refrigerant

**1.3 Details of the supplier of the safety data sheet**

**Supplier**  
GHC Gerling, Holz & Co. Handels GmbH  
Ruhrstraße 113  
D-22761 Hamburg  
Telephone +49 40 853 123 0  
E-mail hamburg@ghc.de

Department responsible for information:  
GHC Gerling, Holz & Co. Handels GmbH  
Telephone +49 40 853 123 0  
Website www.ghc.com

E-mail (competent person):  
msds@ghc.de

**\* 1.4 Emergency telephone number**

EN: Poison Information Center Mainz +49 6131 19240

**\* SECTION 2: Hazards identification**

**\* 2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008 [CLP] Classification procedure

Flam. Gas 1B, H221  
Press. Gas (Liq.), H280

**Hazard statements for physical hazards**  
H221 Flammable gas.  
H280 Contains gas under pressure; may explode if heated.

**\* 2.2 Label elements**

**\* Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**



GHS02

**Signal word**  
Danger

**R 32**

Print date 05.10.2022  
Revision date 05.10.2022  
Version 5.0 (en)  
replaces version of 14.07.2020 (4.0)

**Hazard statements**

H221 Flammable gas.  
H280 Contains gas under pressure; may explode if heated.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.  
P381 In case of leakage, eliminate all ignition sources.  
P403 Store in a well-ventilated place.

\* **Supplemental hazard information**

EIGA0357 Asphyxiant in high concentrations.  
EIGA0787 Contains fluorinated greenhouse gases.  
Please return container with residual pressure.

\* **2.3 Other hazards**\* **Adverse human health effects and symptoms**

Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.  
The inhalation of gas / vapour in high concentrations may cause cardiac arrhythmia.  
Contact with liquid may cause cold burns/frostbite.

\* **Other adverse effects**

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

\* **Results of PBT and vPvB assessment**

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

\* **SECTION 3: Composition / information on ingredients**\* **3.1 Substances**

|                       |                        |
|-----------------------|------------------------|
| <b>Substance name</b> | Difluoromethane (R 32) |
| <b>EC No.</b>         | 200-839-4              |
| <b>REACH No.</b>      | 01-2119471312-47       |
| <b>CAS No.</b>        | 75-10-5                |

**3.2 Mixtures**

not applicable

\* **SECTION 4: First aid measures**\* **4.1 Description of first aid measures****General information**

Remove contaminated, saturated clothing immediately.  
In the event of persistent symptoms obtain medical treatment.  
First aider: Pay attention to self-protection!

**Following inhalation**

Remove casualty to fresh air and keep warm and at rest.  
In case of respiratory standstill give artificial respiration by respiratory bag (Ambu bag) or respirator. Obtain medical assistance..

**Following skin contact**

In case of skin contact rinse with warm water.  
In case of frostbite, wash with plenty of water; do not remove clothing.  
In case of frostbite rinse with lukewarm (not hot) water for at least 15 minutes. Do not remove clothing frozen to the skin.  
Thaw with lukewarm water. Apply a sterile dressing. Obtain medical assistance.

\* **After eye contact**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical assistance.

**R 32**

Print date 05.10.2022  
Revision date 05.10.2022  
Version 5.0 (en)  
replaces version of 14.07.2020 (4.0)

**Following ingestion**

Ingestion is not considered a potential route of exposure.

\* **4.2 Most important symptoms and effects, both acute and delayed**

\* **Symptoms**

The following symptoms may occur in case of strong exposition:

Unconsciousness  
Cardiac arrhythmias  
Dizziness  
Nausea  
Headache

\* **Effects**

Long-term inhaling of separation products may cause pulmonary oedema.

**4.3 Indication of any immediate medical attention and special treatment needed**

**Notes for the doctor**

Treat symptomatically.  
Do not apply drugs of the adrenaline ephedrine group.

\* **SECTION 5: Firefighting measures**

\* **5.1 Extinguishing media**

\* **Suitable extinguishing media**

Extinguishing powder  
Water spray jet  
alcohol resistant foam

\* **Unsuitable extinguishing media**

Full water jet  
Carbon dioxide (CO<sub>2</sub>)

**5.2 Special hazards arising from the substance or mixture**

**Hazardous combustion products**

In case of fire formation of dangerous gases possible.  
Carbon monoxide  
Carbon dioxide (CO<sub>2</sub>)  
Hydrogen fluoride  
Carbonyl fluoride

\* **5.3 Advice for firefighters**

\* **Special protective equipment for firefighters**

Wear a self-contained breathing apparatus and chemical protective clothing.

\* **Additional information**

If possible, shut off gas valves and move containers to a safe location.  
Use water spray jet to protect personnel and to cool endangered containers.  
Exposure to fire may cause rupture / explosion of the containers.  
Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire.  
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

\* **SECTION 6: Accidental release measures**

\* **6.1 Personal precautions, protective equipment and emergency procedures**

\* **For non-emergency personnel**

Use personal protection equipment.  
Leave the danger area.  
Keep people away and stay on the upwind side.

**R 32**

Print date 05.10.2022  
Revision date 05.10.2022  
Version 5.0 (en)  
replaces version of 14.07.2020 (4.0)

\* **For emergency responders**

Personal protection by wearing close-fitting protective clothing and breathing apparatus.  
Pay attention to extension of gas especially at ground (heavier than air) and in direction of the wind.  
Eliminate all ignition sources if safe to do so.  
Remove persons to safety.

\* **6.2 Environmental precautions**

If possible, stop flow of product.  
Do not allow to enter into soil/subsoil.  
Do not allow to enter into surface water or drains.

\* **6.3 Methods and material for containment and cleaning up**

\* **For containment**

If necessary, secure leaky pressure receptacles using a salvage container.  
Prevent the liquid from spreading over a wide area (set up barriers, cover sewage systems).  
Limit expansion of the gas (water spray jet).

\* **For cleaning up**

Leave to vapourize.  
Provide adequate ventilation.

\* **6.4 Reference to other sections**

Disposal: see section 13  
Personal protection equipment: see section 8

\* **SECTION 7: Handling and storage**

\* **7.1 Precautions for safe handling**

\* **Protective measures**

Use only in well-ventilated areas.  
Transfer and handle product only in closed systems.  
Usual measures for fire prevention.  
Containers' temperature should not be increased above 50 °C.  
The working pressure in the receptacle must not exceed the saturation vapour pressure of the pure product resulting at a temperature of 50 °C.  
Prevent cylinders from falling over.  
Take precautionary measures against static discharges. Ground barrels and installations. Use only antistatically equipped (spark-free) tools.  
Use explosion-proof machinery, apparatus, ventilation facilities, tools etc.  
Ensure valve protection device is correctly fitted.  
Ensure valve outlet cap nut or plug (where provided) is correctly fitted.  
Open valve slowly to avoid pressure shock.  
Do not allow backflow into the container.  
Entering of water into the container must be prevented.  
No water to valves, flanges and other fittings.  
Purging of pipes and valves with inert gases - to avoid: water, solvents.

\* **Advices on general occupational hygiene**

When using do not eat, drink, smoke, sniff.  
Wash hands before breaks and after work.  
Remove contaminated clothing and protective equipment before entering eating areas.

\* **7.2 Conditions for safe storage, including any incompatibilities**

\* **Requirements for storage rooms and vessels**

All regulations and local requirements for the storage of containers have to be respected.  
Keep container tightly closed and in a well-ventilated place.  
Containers' temperature should not be increased above 50 °C.  
Prevent cylinders from falling over.  
Only use containers specifically approved for the substance/product.  
Information on suitable materials for receptacles and valves see ISO 11114.

**Storage class**

2A Gases (except aerosol dispensers and lighters)

**R 32**

Print date 05.10.2022  
 Revision date 05.10.2022  
 Version 5.0 (en)  
 replaces version of 14.07.2020 (4.0)

- \* **Materials to avoid**  
 Do not store together with explosives.  
 Do not store together with flammable liquids.  
 Do not store together with flammable solids.  
 Do not store together with pyrophoric and self-heating substances.  
 Do not store together with oxidizing liquids or oxidizing solids.  
 Do not store together with toxic liquids or toxic solids.  
 Do not store together with infectious substances.  
 Do not store together with radioactive material.  
 Do not store together with food or feed.

\* **7.3 Specific end use(s)**

- \* **Recommendation**  
 Use in accordance with regulation (EU) No 517/2014 on fluorinated greenhouse gases.  
 An exposure scenario is not required.

\* **SECTION 8: Exposure controls/personal protection**\* **8.1 Control parameters**\* **DNEL worker**

| CAS No. | Substance name         | DNEL value             | DNEL type                       | Remark   |
|---------|------------------------|------------------------|---------------------------------|--|
| 75-10-5 | Difluoromethane (R 32) | 7035 mg/m <sup>3</sup> | long-term inhalative (systemic) | Assessment factor 7.5, repeated dose toxicity. |

\* **DNEL Consumer**

| CAS No. | Substance name         | DNEL value            | DNEL type                       | Remark  |
|---------|------------------------|-----------------------|---------------------------------|---|
| 75-10-5 | Difluoromethane (R 32) | 750 mg/m <sup>3</sup> | long-term inhalative (systemic) | Assessment factor 25, repeated dose toxicity. |

\* **PNEC**

| CAS No. | Substance name         | PNEC Value     | PNEC type                     | Remark                                     |
|---------|------------------------|----------------|-------------------------------|--|
| 75-10-5 | Difluoromethane (R 32) | 0.142 mg/L     | aquatic, freshwater           | Assessment factor 1000, assessment factor. |
| 75-10-5 | Difluoromethane (R 32) | 0.534 mg/kg dw | sediment, freshwater          |  |
| 75-10-5 | Difluoromethane (R 32) | 1.42 mg/L      | aquatic, intermittent release | Assessment factor 100                      |

\* **8.2 Exposure controls****Appropriate engineering controls**

**Technical measures to prevent exposure**  
 Transfer and handle only in enclosed systems.

\* **Personal protection equipment****Eye/face protection**

Protective goggles according to EN 166, in case of increased risk add protective face shield.

\* **Hand protection**

Safety gloves according to EN 388:  
 Chromate-free leather

**Body protection:**

Safety shoes with steel toecap.  
 Body covering work clothing or chemical resistant suit at increased risk.

**Respiratory protection**

Keep self contained breathing apparatus readily available for emergency use.

Respiratory protection necessary at:

high concentrations

Respiratory protection complying with EN 137.

Do not use any filter apparatus.

In case of rescue and maintenance activities in storage containers use environment-independent breathing apparatus because of risk of suffocation due to displacement of oxygen

**R 32**

Print date 05.10.2022  
 Revision date 05.10.2022  
 Version 5.0 (en)  
 replaces version of 14.07.2020 (4.0)

\* **Thermal hazards**  
 Use cold-resistant protective equipment.

\* **Environmental exposure controls**

\* **Remark**  
 Prevent release to the environment.

\* **SECTION 9: Physical and chemical properties**\* **9.1 Information on basic physical and chemical properties****Physical state**

Gaseous / liquefied under pressure.

**Colour**

colourless

**Odour**

faintly of ether

**Safety relevant basis data**

|  | Value                               | Method     | Source, Remark                        |
|--|-------------------------------------|------------|---------------------------------------|
| Odour threshold:   |                                     |            | not determined                        |
| Melting point/freezing point                             |                                     |            | not applicable                        |
| Boiling point or initial boiling point and boiling range | -51.6 °C<br>pressure 1013 hPa       |            |                                       |
| flammability   |                                     |            | flammable                             |
| Lower and upper explosion limit                          | Upper explosion limit<br>33.4 Vol-% |            |                                       |
| Lower and upper explosion limit                          | Lower explosion limit<br>12.7 Vol-% |            |                                       |
| Flash point  |                                     |            | not applicable                        |
| Auto-ignition temperature                                | 648 °C                              |            |                                       |
| Decomposition temperature                                |                                     |            | No decomposition if used as directed. |
| pH   |                                     |            | not applicable                        |
| Viscosity  |                                     |            | not applicable                        |
| Solubility(ies)  | Water solubility<br>3.65 g/L (25°C) |            |                                       |
| Partition coefficient n-octanol/water (log value)        | 0.21 (25°C)                         | OECD 107   |                                       |
| Vapour pressure  | 14800 hPa (20°C)                    |            |                                       |
| Density and/or relative density                          |                                     |            | not applicable                        |
| Relative vapour density                                  | 1.82                                | Calculated | air = 1                               |
| particle characteristics                                 |                                     |            | not applicable                        |

\* **9.2 Other information**\* **Information with regard to physical hazard classes**\* **Gases under pressure****Safety characteristics**

|                      | Value | Method, Result | Source, Remark |
|----------------------|-------|----------------|----------------|
| Critical temperature | 78 °C |                |                |

\* **Other information**

Vapours are heavier than air.

**R 32**

Print date 05.10.2022  
 Revision date 05.10.2022  
 Version 5.0 (en)  
 replaces version of 14.07.2020 (4.0)

**\* SECTION 10: Stability and reactivity****\* 10.1 Reactivity**

May form an explosive mixture with air.

**\* 10.2 Chemical stability**

The substance is chemically stable under recommended conditions of storage, use and temperature.

**\* 10.3 Possibility of hazardous reactions**

Must not be mixed with air or oxygen.  
 Danger of fire and explosion with oxidants, alkali metals and earth alkali metals.

**\* 10.4 Conditions to avoid**

Heat sources / heat - risk of bursting.  
 Ignition sources, open flames, glowing metal surfaces, etc.

**\* 10.5 Incompatible materials**

Alkali metals  
 Alkaline earth metal  
 Powdered metals  
 Oxidising agent, strong

**\* 10.6 Hazardous decomposition products**

When handled and stored appropriately, no dangerous decomposition products are known.

**\* SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****\* Acute toxicity****\* Animal data**

|                           | Effective dose   | Method, Evaluation | Source, Remark                  |
|---------------------------|--|--------------------|---------------------------------|
| Acute oral toxicity       |  |                    | Study technically not feasible. |
| Acute dermal toxicity     |  |                    | Study technically not feasible. |
| Acute inhalation toxicity | Acute inhalation toxicity (gas)<br>LC0: > 520000 ppm<br>Species Rat<br>Exposure time 4 h | OECD 403           |                                 |

**\* Assessment/classification**

Based on available data, the classification criteria are not met.

**\* Skin corrosion/irritation****\* Other information**

Study technically not feasible.

**\* Serious eye damage/irritation****\* Other information**

Study technically not feasible.

**\* Sensitisation to the respiratory tract****\* Other information**

No data available

**R 32**

Print date 05.10.2022  
 Revision date 05.10.2022  
 Version 5.0 (en)  
 replaces version of 14.07.2020 (4.0)

\* **Skin sensitisation**\* **Other information**

Study technically not feasible.

\* **Repeated dose toxicity (subacute, subchronic, chronic)**

|                                | Effective dose  | Method               | Specific effects: | Organs affected: | Source, Remark |
|--------------------------------|-----------------|----------------------|-------------------|------------------|----------------|
| Subchronic inhalation toxicity | NOAEL 49100 ppm | OECD 413 Species Rat |                   |                  |                |

\* **Assessment/classification**

Based on available data, the classification criteria are not met.

\* **Germ cell mutagenicity**

|                                    | Value | Method   | Result / Evaluation | Remark |
|------------------------------------|-------|----------|---------------------|--------|
| In vitro mutagenicity/genotoxicity |       | OECD 471 |                     |        |
| In vivo mutagenicity/genotoxicity  |       | OECD 474 |                     |        |

\* **Assessment/classification**

Based on available data, the classification criteria are not met.

\* **Carcinogenicity**\* **Other information**

No data available

\* **Reproductive toxicity****Animal data**

|                       | Value                                   | Method   | Result / Evaluation | Remark                          |
|-----------------------|---|----------|---------------------|---------------------------------|
| Reproductive toxicity | inhalative NOEL 50000 ppm Species Mouse | OECD 478 |                     | Analogous to a similar product. |

\* **Assessment/classification**

Based on available data, the classification criteria are not met.

\* **STOT-single exposure**\* **STOT SE 1 and 2**\* **Assessment/classification**

Based on available data, the classification criteria are not met.

\* **STOT-repeated exposure**\* **Assessment/classification**

Based on available data, the classification criteria are not met.

\* **Aspiration hazard**\* **Assessment/classification**

Study technically not feasible.

**11.2 Information on other hazards****Symptoms related to the physical, chemical and toxicological characteristics**\* **Additional information**

The inhalation of gas / vapour in high concentrations may cause cardiac arrhythmia. Inhalation causes narcotic effects/intoxication.



**R 32**

Print date 05.10.2022  
 Revision date 05.10.2022  
 Version 5.0 (en)  
 replaces version of 14.07.2020 (4.0)

**\* SECTION 12: Ecological information****12.1 Toxicity****Aquatic toxicity**

|   | Effective dose   | Method,Evaluation | Source, Remark |
|---|--|-------------------|----------------|
| Acute (short-term) fish toxicity                                | LC50: 1507 mg/L Species freshwater fish<br>Test duration 96 h              | QSAR              |                |
| Chronic (long-term) fish toxicity                               | not determined   |                   |                |
| Acute (short-term) toxicity to crustacea                        | EC50 652 mg/L Species Daphnia magna (Big water flea)<br>Test duration 48 h | QSAR              |                |
| Chronic (long-term) toxicity to aquatic invertebrate            | not determined   |                   |                |
| Acute (short-term) toxicity to algae and cyanobacteria          | EC50 142 mg/L Species Algae<br>Test duration 96 h                          | QSAR              |                |
| Chronic (long-term) toxicity to aquatic algae and cyanobacteria | not determined   |                   |                |
| Toxicity to other aquatic plants/organisms                      | not determined   |                   |                |
| Toxicity to microorganisms                                      | not determined   |                   |                |

**\* 12.2 Persistence and degradability**

|                | Value                                      | Method     | Source, Remark                           |
|----------------|--|------------|--|
| Biodegradation | Degradation rate 5 %<br>Test duration 28 d | OECD 301 D | CAS No.75-10-5<br>Difluoromethane (R 32) |

**\* Assessment/classification**  
 Not readily biodegradable (according to OECD criteria)

**\* 12.3 Bioaccumulative potential**

**\* Assessment/classification**  
 Based on the n-octanol/water partition coefficient accumulation in organisms is not expected.

**\* 12.4 Mobility in soil**

|                        | Value  | Distribution | Transport type | Method    | Remark |
|------------------------|--|--------------|----------------|-----------|--------|
| Half-life time in soil | CAS No.75-10-5<br>Difluoromethane (R 32)<br>21.73 L/kg |              |                | KOC value |        |

**\* Assessment/classification**  
 Based on available data, the classification criteria are not met.

**\* 12.5 Results of PBT and vPvB assessment**

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

**\* 12.6 Endocrine disrupting properties**

|                                 | Effective dose | Method,Evaluation | Source, Remark  |
|---------------------------------|----------------|-------------------|-----------------|
| Endocrine disrupting properties |                |                   | See section 2.3 |

**\* 12.7 Other adverse effects**

|                                  | Value | Method | Source, Remark |
|----------------------------------|-------|--------|----------------|
| Ozone depletion potential (ODP): | 0     |        |                |
| Global warming potential (GWP)   | 675   |        |                |

**R 32**

Print date 05.10.2022  
 Revision date 05.10.2022  
 Version 5.0 (en)  
 replaces version of 14.07.2020 (4.0)

**\* SECTION 13: Disposal considerations****\* 13.1 Waste treatment methods****Waste codes/waste designations according to EWC/AVV**

| Waste code product | Waste name                     |
|--------------------|--------------------------------|
| 140601 *           | chlorofluorocarbons, HCFC, HFC |

**\* Appropriate disposal / Product**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.  
 Prevent release to the environment. No disposal via the sewage.  
 Disposal according to local regulations.

**Appropriate disposal / Package**

Transportable pressure equipment (empty, residual pressure): Return to supplier / manufacturer.

**\* SECTION 14: Transport information**

|  | Land transport (ADR/RID)             | Sea transport (IMDG)                   | Air transport (ICAO-TI / IATA-DGR)     |
|--|--------------------------------------|--|--|
| <b>14.1 UN number or ID number</b>     | 3252                                 | 3252                                   | 3252                                   |
| <b>14.2 UN proper shipping name</b>    | REFRIGERANT GAS R 32 (Difluormethan) | REFRIGERANT GAS R 32 (Difluoromethane) | Refrigerant gas R 32 (Difluoromethane) |
| <b>14.3 Transport hazard class(es)</b> | 2                                    | 2.1                                    | 2.1                                    |
| <b>14.4 Packing group</b>              | -                                    | -                                      | -                                      |
| <b>14.5 Environmental hazards</b>      | No                                   | No                                     | No                                     |

**14.6 Special precautions for user**

The protective measures listed in Sections 6, 7 and 8 of the Safety Data Sheet have to be considered.

**14.7 Maritime transport in bulk according to IMO instruments**

No carriage in bulk.

**Land transport (ADR/RID)**

|                            |                                      |
|----------------------------|--------------------------------------|
| UN number or ID number     | 3252                                 |
| UN proper shipping name    | REFRIGERANT GAS R 32 (Difluormethan) |
| Transport hazard class(es) | 2                                    |
| Hazard label(s)            | 2.1                                  |
| Classification code        | 2F                                   |
| Packing group              | -                                    |
| Environmental hazards      | No                                   |
| Limited quantity (LQ)      | 0                                    |
| Special provisions         | 662                                  |
| Tunnel restriction code    | B/D                                  |

**\* Sea transport (IMDG)**

|                            |  |
|----------------------------|--|
| UN number or ID number     | 3252                                   |
| UN proper shipping name    | REFRIGERANT GAS R 32 (Difluoromethane) |
| Transport hazard class(es) | 2.1                                    |
| Packing group              | -                                      |
| Environmental hazards      | No                                     |
| Limited quantity (LQ)      | 0                                      |
| Marine pollutant           | No                                     |

**R 32**

Print date 05.10.2022  
 Revision date 05.10.2022  
 Version 5.0 (en)  
 replaces version of 14.07.2020 (4.0)

EmS F-D, S-U

**\* Air transport (ICAO-TI / IATA-DGR)**

UN number or ID number 3252  
 UN proper shipping name Refrigerant gas R 32 (Difluoromethane)  
 Transport hazard class(es) 2.1  
 Packing group -  
 Environmental hazards No

**\* SECTION 15: Regulatory information****\* 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****\* EU legislation****\* Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.  
 Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

**\* Other regulations (EU)****\* To follow:**

Regulation (EU) No 517/2014 on fluorinated greenhouse gases.  
 Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), Annex XVII No 40.  
 Regulation (EU) 2015/2068 establishing, pursuant to Regulation (EU) No 517/2014, the format of labels for products and equipment containing fluorinated greenhouse gases.  
 Regulation (EU) 2015/2067 establishing, pursuant to Regulation (EU) No 517/2014, ~ certification ~ as regards stationary refrigeration, air conditioning and heat pump equipment, and ~ containing fluorinated greenhouse gases.  
 Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances.  
 National and local regulations concerning chemicals shall be observed.

**\* Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive] VOC**

VOC-value  $\geq 99\%$

**\* 15.2 Chemical Safety Assessment****\* National regulations**

For this substance a chemical safety assessment has been carried out.

**\* SECTION 16: Other information****Key literature references and sources for data**

Information from our suppliers and data from the "GESTIS Substances Database" and the "Registered Substances" database of the European Chemicals Agency (ECHA) were used to create this safety data sheet.

**\* Additional information**

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

**Relevant H- and EUH-phrases (Number and full text)**

H221 Flammable gas.  
 H280 Contains gas under pressure; may explode if heated.

**Indication of changes**

\* Data changed compared with the previous version