R 134a

19.09.2022 19.09.2022 Print date Revision date 18.0 (en) Version replaces version of 07.03.2018 (17.0)



* SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name/designation R 134a Art-Nr(n). 0046, 0015

Substance name 1,1,1,2-Tetrafluoroethane (R 134a)

EC No. 212-377-0

REACH No. 01-2119459374-33

CAS No. 811-97-2

* 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Refrigerant Laboratory chemical Aerosol propellants

* 1.3 Details of the supplier of the safety data sheet

Supplier GHC Gerling, Holz & Co. Handels GmbH Ruhrstraße 113 D-22761 Hamburg Telephone +49 40 853 123 0 E-mail hamburg@ghc.de

Department responsible for information: GHC Gerling, Holz & Co. Handels GmbH Telephone +49 40 853 123 0 Website www.ghc.com

E-mail (competent person): msds@ghc.de

* 1.4 Emergency telephone number

EN: Poison Information Center Mainz +49 6131 19240

* SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Classification procedure

Press. Gas (Liq.), H280

Hazard statements for physical hazards

H280 Contains gas under pressure; may explode if heated.

- * 2.2 Label elements
- * Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



GHS04

Signal word Warning

R 134a

Print date 19.09.2022
Revision date 19.09.2022
Version 18.0 (en) replaces version of 07.03.2018 (17.0)



the chemical gas specialist

Hazard statements

H280 Contains gas under pressure; may explode if heated.

Precautionary statements

P403 Store in a well-ventilated place.

* Supplemental hazard information

EIGA0357 Asphyxiant in high concentrations. EIGA0787 Contains fluorinated greenhouse gases. Please return container with residual pressure.

* 2.3 Other hazards

* Adverse human health effects and symptoms

Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level. The inhalation of gas / vapour in high concentrations may cause cardiac arrhythmia. Contact with liquid may cause cold burns/frostbite.

Other adverse effects

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

* Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

* SECTION 3: Composition / information on ingredients

* 3.1 Substances

Substance name 1,1,1,2-Tetrafluoroethane (R 134a)

EC No. 212-377-0

REACH No. 01-2119459374-33

CAS No. 811-97-2

3.2 Mixtures

not applicable

* SECTION 4: First aid measures

* 4.1 Description of first aid measures

* General information

Remove contaminated, saturated clothing immediately. In the event of persistent symptoms obtain medical treatment. First aider: Pay attention to self-protection!

* Following inhalation

Remove casualty to fresh air and keep warm and at rest.

In case of respiratory standstill give artificial respiration by respiratory bag (Ambu bag) or respirator. Obtain medical assistance..

Following skin contact

In case of skin contact rinse with warm water.

In case of frostbite, wash with plenty of water; do not remove clothing.

In case of frostbite rinse with lukewarm (not hot) water for at least 15 minutes. Do not remove clothing frozen to the skin. Thaw with lukewarm water. Apply a sterile dressing. Obtain medical assistance.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical assistance.

Following ingestion

Ingestion is not considered a potential route of exposure.

R 134a

Print date 19.09.2022 Revision date 19.09.2022 18.0 (en) Version replaces version of 07.03.2018 (17.0)



4.2 Most important symptoms and effects, both acute and delayed

Symptoms

The following symptoms may occur in case of strong exposition: Unconsciousness

Cardiac arrhythmias

Dizziness Nausea

Headache

Effects

Long-term inhaling of separation products may cause pulmonary oedema.

* 4.3 Indication of any immediate medical attention and special treatment needed

Notes for the doctor

Treat symptomatically

Do not apply drugs of the adrenaline ephedrine group.

* SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

The product itself does not burn. The product itself does not burn. Match extinguishing measures to surrounding fire. Extinguishing powder Water spray jet alcohol resistant foam

Carbon dioxide (CO2)

Unsuitable extinguishing media

Full water jet

* 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

In case of fire formation of dangerous gases possible. Carbon monoxide Carbon dioxide (CO2) Hydrogen fluoride Carbonyl fluoride

* 5.3 Advice for firefighters

Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

* Additional information

If possible, shut off gas valves and move containers to a safe location.

Use water spray jet to protect personnel and to cool endangered containers. Exposure to fire may cause rupture / explosion of the containers.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

* SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Use personal protection equipment.

Leave the danger area.

Keep people away and stay on the upwind side.

For emergency responders

Personal protection by wearing close-fitting protective clothing and breathing apparatus.

Pay attention to extension of gas especially at ground (heavier than air) and in direction of the wind.

Remove persons to safety.

R 134a

Print date 19.09.2022 Revision date 19.09.2022 18.0 (en) Version replaces version of 07.03.2018 (17.0)



the chemical gas specialist

6.2 Environmental precautions

If possible, stop flow of product. Do not allow to enter into soil/subsoil.

Do not allow to enter into surface water or drains.

* 6.3 Methods and material for containment and cleaning up

For containment

If necessary, secure leaky pressure receptacles using a salvage container.

Prevent the liquid from spreading over a wide area (set up barriers, cover sewage systems).

Limit expansion of the gas (water spray jet).

For cleaning up

Leave to vapourize.

Provide adequate ventilation.

6.4 Reference to other sections

Disposal: see section 13

Personal protection equipment: see section 8

* SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Use only in well-ventilated areas.

Transfer and handle product only in closed systems.

Usual measures for fire prevention.

Containers' temperature should not be increased above 50 °C.

The working pressure in the receptacle must not exceed the saturation vapour pressure of the pure product resulting at a temperature of 50 °C.

Prevent cylinders from falling over.

Ensure valve protection device is correctly fitted.

Ensure valve outlet cap nut or plug (where provided) is correctly fitted.

Open valve slowly to avoid pressure shock. Do not allow backflow into the container.

Entering of water into the container must be prevented.

No water to valves, flanges and other fittings.

Purging of pipes and valves with inert gases - to avoid: water, solvents.

Advices on general occupational hygiene

When using do not eat, drink, smoke, sniff.

Wash hands before breaks and after work.

Remove contaminated clothing and protective equipment before entering eating areas.

* 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

All regulations and local requirements for the storage of containers have to be respected. Keep container tightly closed and in a well-ventilated place.

Containers' temperature should not be increased above 50 °C.

Prevent cylinders from falling over.

Only use containers specifically approved for the substance/product.

Information on suitable materials for receptacles and valves see ISO 11114.

Storage class

2A Gases (except aerosol dispensers and lighters)

Materials to avoid

Do not store together with explosives.

Do not store together with flammable liquids.

Do not store together with flammable solids.

Do not store together with pyrophoric and self-heating substances. Do not store together with oxidizing liquids or oxidizing solids.

Do not store together with toxic liquids or toxic solids.

Do not store together with infectious substances.

Do not store together with radioactive material.

Do not store together with food or feed.

R 134a

19.09.2022 19.09.2022 Print date Revision date 18.0 (en) Version replaces version of 07.03.2018 (17.0)



the chemical gas specialist

7.3 Specific end use(s)

Recommendation

Use in accordance with regulation (EU) No 517/2014 on fluorinated greenhouse gases. An exposure scenario is not required.

* SECTION 8: Exposure controls/personal protection

8.1 Control parameters

DNEL worker

CAS No.	Substance name	DNEL value	DNEL type	Remark
811-97-2	1,1,1,2-Tetrafluoroethane (R 134a) 13936 mg/m³	long-term inhalative (systemic)	Assessment factor 7.5, repeated dose toxicity.
DNEL Cor	sumer			
CAS No.	Substance name	DNEL value	DNEL type	Remark
811-97-2	1,1,1,2-Tetrafluoroethane (R 134a) 2476 mg/m³	long-term inhalative (systemic)	Assessment factor 15, repeated dose toxicity.

PNEC

CAS No.	Substance name	PNEC Value	PNEC type	Remark
811-97-2	1,1,1,2-Tetrafluoroethane (R 134a) 0.01 mg/L	aquatic, marine water	Assessment factor 10000, assessment factor.
811-97-2	1,1,1,2-Tetrafluoroethane (R 134a) 0.1 mg/L	aquatic, freshwater	Assessment factor 1000, assessment factor.
811-97-2	1,1,1,2-Tetrafluoroethane (R 134a) 0.75 mg/kg dw	sediment, freshwater	
811-97-2	1,1,1,2-Tetrafluoroethane (R 134a) 1 mg/L	aquatic, intermittent release	Assessment factor 100, assessment factor.
811-97-2	1,1,1,2-Tetrafluoroethane (R 134a) 73 mg/L	sewage treatment plant (STP)	Assessment factor 10, assessment factor.

* 8.2 Exposure controls

Appropriate engineering controls

Technical measures to prevent exposure Transfer and handle only in enclosed systems.

Personal protection equipment

Eye/face protection

Protective goggles according to EN 166, in case of increased risk add protective face shield.

Hand protection

Safety gloves according to EN 388:

Chromate-free leather

Body protection:

Safety shoes with steel toecap.

Body covering work clothing or chemical resistant suit at increased risk.

Respiratory protectionKeep self contained breathing apparatus readily available for emergency use.
Respiratory protection necessary at:

high concentrations

Respiratory protection complying with EN 137.

Do not use any filter apparatus.

In case of rescue and maintenance activities in storage containers use environment-independent breathing apparatus because of risk of suffocation due to displacement of oxygen

Thermal hazards

Use cold-resistant protective equipment.

R 134a

Print date Revision date 19.09.2022 19.09.2022 18.0 (en) Version replaces version of 07.03.2018 (17.0)



Environmental exposure controls

Remark

Prevent release to the environment.

* SECTION 9: Physical and chemical properties

* 9.1 Information on basic physical and chemical properties

Physical stateGaseous / liquefied under pressure.

Colour

colourless

Odour

faintly of ether

Safety relevant basis data

	Value	Method	Source, Remark
Odour threshold:			not determined
Melting point/freezing point			not applicable
Boiling point or initial boiling point and boiling range	-26 °C pressure 1013 hPa		
flammability			none
Lower and upper explosion limit			none
Flash point			not applicable
Auto-ignition temperature			not determined
Decomposition temperature	> 370 °C		
рН			not applicable
Viscosity			not applicable
Solubility(ies)	Water solubility 1 g/L (25°C)		
Partition coefficient n-octanol/water (log value)	1.06 (25°C)	OECD 107	
Vapour pressure	5740 hPa (20°C)		
Density and/or relative density			not applicable
Relative vapour density	3.52 (25°C)		air = 1
particle characteristics			not applicable

* 9.2 Other information

Information with regard to physical hazard classes

Gases under pressure

Safety characteristics

	Value	Method, Result	Source, Remark
Critical temperature	101 °C		

Other information

Vapours are heavier than air.

R 134a

19.09.2022 19.09.2022 Print date Revision date 18.0 (en) Version replaces version of 07.03.2018 (17.0)



* SECTION 10: Stability and reactivity

* 10.1 Reactivity

The product is not flammable in air under ambient conditions of temperature and pressure. When pressurised with air, oxygen or other oxidants, it may become flammable.

* 10.2 Chemical stability

The substance is chemically stable under recommended conditions of storage, use and temperature.

* 10.3 Possibility of hazardous reactions

Must not be mixed with air or oxygen. Danger of fire and explosion with oxidants, alkali metals and earth alkali metals.

10.4 Conditions to avoid

Heat sources / heat - risk of bursting. Ignition sources, open flames, glowing metal surfaces, etc.

* 10.5 Incompatible materials

Alkali metals Alkaline earth metal Powdered metals Oxidising agent, strong

* 10.6 Hazardous decomposition products

When handled and stored appropriately, no dangerous decomposition products are known.

* SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Animal data

	Effective dose	Method,Evaluation	Source, Remark
Acute oral toxicity			Study technically not feasible.
Acute dermal toxicity			Study technically not feasible.
Acute inhalation toxicity	LCLo ≥ 567000 ppm Species Rat Exposure time 4 h	OECD 403	

Assessment/classification

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Other information

Study technically not feasible.

Serious eye damage/irritation

Other information

Study technically not feasible.

Sensitisation to the respiratory tract

Assessment/classification non-sensitizing; Laboratory animals

Skin sensitisation

Other information

Study technically not feasible.

R 134a

Print date 19.09.2022
Revision date 19.09.2022
Version 18.0 (en)
replaces version of 07.03.2018 (17.0)



the chemical gas specialist

* Repeated dose toxicity (subacute, subchronic, chronic)

Effective dose Method Specific effects: Organs affected: Source, Remark

Chronic inhalation NOAEC 50000 OECD 453

toxicity ppm Species Rat

* Additional information

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Value Method Result / Evaluation Remark

In vitro
mutagenicity/genotox
icity

In vivo Species Rat
mutagenicity/genotox
icity

OECD 486
mutagenicity/genotox
icity

* Assessment/classification

Based on available data, the classification criteria are not met.

* Carcinogenicity

Animal data

	Value	Method	Result / Evaluation	Remark
Carcinogenicity	inhalative NOEL(C): 10000 ppm Species Rat Exposure duration 2 a	OECD 453		

* Assessment/classification

Based on available data, the classification criteria are not met.

* Reproductive toxicity

* Animal data

	Value	Method	Result / Evaluation	Remark
Reproductive toxicity	inhalative NOEL 50000 ppm Species Mouse	OECD 478		

Assessment/classification

Based on available data, the classification criteria are not met.

* STOT-single exposure

* STOT SE 1 and 2

Assessment/classification

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Assessment/classification

Based on available data, the classification criteria are not met.

Aspiration hazard

* Assessment/classification

Study technically not feasible.

11.2 Information on other hazards

* Symptoms related to the physical, chemical and toxicological characteristics

* Additional information

The inhalation of gas / vapour in high concentrations may cause cardiac arrhythmia. Inhalation causes narcotic effects/intoxication.

R 134a

Print date Revision date 19.09.2022 19.09.2022 18.0 (en) Version replaces version of 07.03.2018 (17.0)



* SECTION 12: Ecological information

* 12.1 Toxicity

Aquatic toxicity

•	•	Effective dose	Method,Evaluation	Source, Remark
	Acute (short-term) fish toxicity	LC50: 450 mg/L Species Oncorhynchus mykiss (Rainbow trout) Test duration 96 h	EU Method C.1	
	Chronic (long-term) fish toxicity	not determined		
	Acute (short-term) toxicity to crustacea	EC50 980 mg/L Species Daphnia magna (Big water flea) Test duration 48 h	EU Method C.2	
	Chronic (long-term) toxicity to aquatic invertebrate	not determined		
	Acute (short-term) toxicity to algae and cyanobacteria	EC50 > 118 mg/L Species Pseudokirchneriella subcapitata Test duration 72 h	EU Method C.3	Analogous to a similar product.
	Chronic (long-term) toxicity to aquatic algae and cyanobacteria	not determined		
	Toxicity to other aquatic plants/organisms	not determined		
	Toxicity to microorganisms	EC50 > 730 mg/L Species growth of Ps. putida Test duration 6 h		
* 12.2 F	Persistence and degradability			
		Value	Method	Source, Remark
	Biodegradation	Degradation rate 3 % Test duration 28 d	OECD 301 D	CAS No.811-97-2 1,1,1,2- Tetrafluoroethane (R 134a)

Assessment/classification Not readily biodegradable (according to OECD criteria)

* 12.3 Bioaccumulative potential

Based on the n-octanol/water partition coefficient accumulation in organisms is not expected.

* 12.4 Mobility in soil

	Value	Distribution	Transport type	Method	Remark
Half-life time in soil	CAS No.811-97- 2 1,1,1,2- Tetrafluoroethan e (R 134a) 37.26 L/kg			KOC value	

* 12.5 Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

* 12.6 Endocrine disrupting properties

	Effective dose	Method,Evaluation	Source, Remark
Endocrine disrupting properties			See section 2.3

* 12.7 Other adverse effects

	Value	Method	Source, Remark
Ozone depletion potential (ODP):	0		
Global warming notential (GWP)	1430		

R 134a

Print date 19.09.2022
Revision date 19.09.2022
Version 18.0 (en) replaces version of 07.03.2018 (17.0)



* SECTION 13: Disposal considerations

* 13.1 Waste treatment methods

Waste codes/waste designations according to EWC/AVV

Waste code product Waste name

140601 * chlorofluorocarbons, HCFC, HFC

* Appropriate disposal / Product

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Prevent release to the environment. No disposal via the sewage.

Disposal according to local regulations.

Appropriate disposal / Package

Transportable pressure equipment (empty, residual pressure): Return to supplier / manufacturer.

* SECTION 14: Transport information

	Land transport (ADR/RID)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA- DGR)
14.1 UN number or ID number	3159	3159	3159
14.2 UN proper shipping name	REFRIGERANT GAS R 134a (1,1,1,2- TETRAFLUORETHAN)	REFRIGERANT GAS R 134a (1,1,1,2- TETRAFLUOROETHANE)	Refrigerant gas R 134a (1,1,1,2- TETRAFLUOROETHANE)
14.3 Transport hazard class(es)	2	2.2	2.2
14.4 Packing group	-	-	-
14.5 Environmental hazards	No	No	No

14.6 Special precautions for user

The protective measures listed in Sections 6, 7 and 8 of the Safety Data Sheet have to be considered.

14.7 Maritime transport in bulk according to IMO instruments

No carriage in bulk.

Land transport (ADR/RID)

UN number or ID number 3159

UN proper shipping name REFRIGERANT GAS R 134a (1,1,1,2-TETRAFLUORETHAN)

Transport hazard class(es) 2
Hazard label(s) 2.2
Classification code 2A
Packing group Environmental hazards No
Limited quantity (LQ) 120 ml
Special provisions 662
Tunnel restriction code C/E

* Sea transport (IMDG)

UN number or ID number 3159

UN proper shipping name REFRIGERANT GAS R 134a (1,1,1,2-TETRAFLUOROETHANE)

Transport hazard class(es) 2.2
Packing group Environmental hazards No
Limited quantity (LQ) 120 ml

R 134a

Print date 19.09.2022 Revision date 19.09.2022 18.0 (en) Version replaces version of 07.03.2018 (17.0)



the chemical gas specialist

Marine pollutant Nο FmS F-C, S-V

Air transport (ICAO-TI / IATA-DGR)

UN number or ID number 3159

UN proper shipping name Refrigerant gas R 134a (1,1,1,2-TETRAFLUOROETHANE)

Transport hazard class(es) Packing group Environmental hazards Nο

* SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations (EU)

To follow:

Regulation (EU) No 517/2014 on fluorinated greenhouse gases.

Regulation (EU) 2015/2068 establishing, pursuant to Regulation (EU) No 517/2014, the format of labels for products and

equipment containing fluorinated greenhouse gases.

Regulation (EU) 2015/2067 establishing, pursuant to Regulation (EU) No 517/2014, ~ certification ~ as regards stationary refrigeration, air conditioning and heat pump equipment, and ~ containing fluorinated greenhouse gases.

National and local regulations concerning chemicals shall be observed.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive] VOC VOC-value ≥ 99 %

* 15.2 Chemical Safety Assessment

National regulations

For this substance a chemical safety assessment has been carried out.

* SECTION 16: Other information

Key literature references and sources for dataInformation from our suppliers and data from the "GESTIS Substances Database" and the "Registered Substances" database of the European Chemicals Agency (ECHA) were used to create this safety data sheet.

Additional information

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Relevant H- and EUH-phrases (Number and full text)

H280 Contains gas under pressure; may explode if heated.

Indication of changes

Data changed compared with the previous version