

**Mixture 90 % Ethylene oxide / 10 % Carbon dioxide**

Print date 08.07.2025  
Revision date 08.07.2025  
Version 16.0 (en)  
replaces version of 21.12.2022 (15.0)

**\* SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

**Trade name/designation** Mixture 90 % Ethylene oxide / 10 % Carbon dioxide  
**Art-Nr(n).** 5110  
**Unique Formula Identifier** UFI: 7N6N-TFTU-3104-ANAU

**Hazard components**  
ethylene oxide

**\* 1.2 Relevant identified uses of the substance or mixture and uses advised against**

**\* Use of the substance/mixture**  
Basic substance  
laboratory reagent  
Sterilisation of medical devices, medicinal products and their (empty) packaging

**Uses advised against**  
Use as a biocidal product

**1.3 Details of the supplier of the safety data sheet**

**Supplier**  
GHC Gerling, Holz & Co. Handels GmbH  
Ruhrstraße 113  
D-22761 Hamburg  
Telephone +49 40 853 123 0  
E-mail hamburg@ghc.de  
Website www.ghc.com

Department responsible for information:  
GHC Gerling, Holz & Co. Handels GmbH  
Telephone +49 40 853 123 0

E-mail (competent person):  
msds@ghc.de

**1.4 Emergency telephone number**

EN: Poison Information Center Mainz +49 6131 19240

**\* SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008 [CLP]	Classification procedure
--	--------------------------

Chem. Unst. Gas A, H220

Chem. Unst. Gas A, H230

Press. Gas (Liq.), H280

Acute Tox. 3, H301

Acute Tox. 3, H331

Skin Corr. 1, H314

Eye Dam. 1, H318

Muta. 1B, H340

Carc. 1B, H350i

Repr. 1B, H360Fd

STOT SE 3, H335

STOT SE 3, H336

STOT RE 1, H372

**Mixture 90 % Ethylene oxide / 10 % Carbon dioxide**

Print date 08.07.2025  
Revision date 08.07.2025  
Version 16.0 (en)  
replaces version of 21.12.2022 (15.0)

**Hazard statements for physical hazards**

H220 Extremely flammable gas.  
H230 May react explosively even in the absence of air.  
H280 Contains gas under pressure; may explode if heated.

**Hazard statements for health hazards**

H301 Toxic if swallowed.  
H314 Causes severe skin burns and eye damage.  
H318 Causes serious eye damage.  
H331 Toxic if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H340 May cause genetic defects.  
H350i May cause cancer by inhalation.  
H360Fd May damage fertility. Suspected of damaging the unborn child.  
H372 Causes damage to the nervous system and to blood forming organs through prolonged or repeated exposure by inhalation.

**2.2 Label elements**

**Labelling according to Regulation (EC) No 1272/2008 [CLP]**

**Hazard components**

ethylene oxide

**Hazard pictograms**



GHS02



GHS05



GHS06



GHS08

**Signal word**

Danger

**Hazard statements**

H220 Extremely flammable gas.  
H230 May react explosively even in the absence of air.  
H280 Contains gas under pressure; may explode if heated.  
H301 Toxic if swallowed.  
H314 Causes severe skin burns and eye damage.  
H331 Toxic if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H340 May cause genetic defects.  
H350i May cause cancer by inhalation.  
H360Fd May damage fertility. Suspected of damaging the unborn child.  
H372 Causes damage to the nervous system and to blood forming organs through prolonged or repeated exposure by inhalation.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe gas/vapours.  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.

**Supplemental hazard information**

EIGA0803 Restricted to professional users.  
Please return container with residual pressure.  
Withdrawal out of the liquid phase only.

**\* 2.3 Other hazards**

**\* Adverse human health effects and symptoms**

The product is skin resorptive.  
Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.  
Contact with liquid may cause cold burns/frostbite.

**Mixture 90 % Ethylene oxide / 10 % Carbon dioxide**

Print date 08.07.2025  
 Revision date 08.07.2025  
 Version 16.0 (en)  
 replaces version of 21.12.2022 (15.0)

**Other adverse effects**

The substance/mixture does not contain components identified as having endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1% or more.

**Results of PBT and vPvB assessment**

The substance/mixture does not contain components meeting the PBT/vPvB criteria of the Reach Regulation, Annex XIII, at levels of 0.1% or higher.

**SECTION 3: Composition / information on ingredients****3.1 Substances**

not applicable

**3.2 Mixtures****Hazardous ingredients**

CAS No	EC No	Index No	Substance name	Concentration	Classification according to Regulation (EC) No 1272/2008 [CLP]	SCL/ M/ ATE
75-21-8	200-849-9	603-023-00-X	ethylene oxide	90 weight-%	Chem. Unst. Gas A; H220 H230 Press. Gas (Liq.); H280 Acute Tox. 3 ; H301 Acute Tox. 3; H331 Skin Corr. 1; H314 Eye Dam. 1; H318 Muta. 1B; H340 Carc. 1B; H350i(inhalation) Repr. 1B; H360Fd STOT SE 3; H335 STOT SE 3; H336 STOT RE 1; H372	Acute Tox. 3; H301: ATE = 100 mg/kg Acute Tox. 3; H331: ATE = 700 ppm
124-38-9	204-696-9		Carbon dioxide	10 weight-%	Press. Gas (Liq.); H280	

REACH No.	Substance name
01-2119432402-53	ethylene oxide
-	Carbon dioxide

**Remark**

The text of the H-and EUH-phrases is shown in section 16.

Carbon dioxide is, in accordance with Article 2(7) in conjunction with Annex IV of Regulation (EC) No 1907/2006 [REACH], exempt from registration.

**SECTION 4: First aid measures****4.1 Description of first aid measures****General information**

First aider: Pay attention to self-protection!

Remove contaminated, saturated clothing immediately.

Call a physician immediately.

Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

**Following inhalation**

Remove casualty to fresh air and keep warm and at rest.

In the event of pulmonary irritation treat initially with corticoid spray, e.g. Ventolair- or Pulmicort- metered-dose aerosol (Ventolair and Pulmicort are registered trademarks).

In case of respiratory arrest give artificial respiration by respiratory bag (Ambu bag) or respirator. Obtain medical assistance.

**Mixture 90 % Ethylene oxide / 10 % Carbon dioxide**

Print date 08.07.2025  
Revision date 08.07.2025  
Version 16.0 (en)  
replaces version of 21.12.2022 (15.0)

**Following skin contact**

In case of skin contact rinse with warm water.  
In case of frostbite, wash with plenty of water; do not remove clothing.  
In case of frostbite rinse with lukewarm (not hot) water for at least 15 minutes. Do not remove clothing frozen to the skin.  
Thaw with lukewarm water. Apply a sterile dressing. Obtain medical assistance.

**After eye contact**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical assistance.

**Following ingestion**

Do NOT induce vomiting.  
Rinse mouth immediately and drink plenty of water.

**4.2 Most important symptoms and effects, both acute and delayed**

**Symptoms**

Dyspnoea  
Depression of central nervous system  
Vomiting  
Redness / blebs on the skin.

**Effects**

Risk of bullous dermatitis on exposure to vapors.  
Pulmonary oedema

**4.3 Indication of any immediate medical attention and special treatment needed**

**Notes for the doctor**

Treat symptomatically.  
Pulmonary oedema prophylaxis.

**SECTION 5: Firefighting measures**

**5.1 Extinguishing media**

**Suitable extinguishing media**

Extinguishing powder  
alcohol resistant foam  
Water spray jet

**Unsuitable extinguishing media**

Full water jet  
Carbon dioxide (CO<sub>2</sub>)

**5.2 Special hazards arising from the substance or mixture**

**Hazardous combustion products**

In case of fire formation of dangerous gases possible.  
Carbon monoxide  
Carbon dioxide (CO<sub>2</sub>)

**5.3 Advice for firefighters**

**Special protective equipment for firefighters**

Wear a self-contained breathing apparatus and chemical protective clothing.

**Additional information**

If possible, shut off gas valves and move containers to a safe location.  
Use water spray jet to protect personnel and to cool endangered containers.  
Exposure to fire may cause rupture / explosion of the containers.  
Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire.  
Dispose of fire residues and contaminated extinguishing water in accordance with local, official regulations.

**Mixture 90 % Ethylene oxide / 10 % Carbon dioxide**

Print date 08.07.2025  
Revision date 08.07.2025  
Version 16.0 (en)  
replaces version of 21.12.2022 (15.0)

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel**

Use personal protection equipment.  
Leave the danger area.  
Keep people away and stay on the upwind side.

**For emergency responders**

Personal protection by wearing close-fitting protective clothing and breathing apparatus.  
Pay attention to extension of gas especially at ground (heavier than air) and in direction of the wind.  
Eliminate all ignition sources if safe to do so.  
Remove persons to safety.

### 6.2 Environmental precautions

If possible, stop flow of product.  
Do not allow to enter into soil/subsoil.  
Do not allow to enter into surface water or drains.

### 6.3 Methods and material for containment and cleaning up

**For containment**

If necessary, secure leaky pressure receptacles using a salvage container.  
Prevent the liquid from spreading over a wide area (set up barriers, cover sewage systems).  
Limit expansion of the gas (water spray jet).

**For cleaning up**

Leave to vapourize.  
Provide adequate ventilation.

### 6.4 Reference to other sections

Disposal: see section 13  
Personal protection equipment: see section 8

## \* SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

**Protective measures**

Use only in well-ventilated areas.  
Transfer and handle product only in closed systems.  
Usual measures for fire prevention.  
Containers' temperature should not be increased above 50 °C.  
The working pressure in the receptacle must not exceed the saturation vapour pressure of the pure product resulting at a temperature of 50 °C.  
Prevent cylinders from falling over.  
Take precautionary measures against static discharges. Ground barrels and installations. Use only antistatically equipped (spark-free) tools.  
Use explosion-proof machinery, apparatus, ventilation facilities, tools etc.  
Ensure valve protection device is correctly fitted.  
Ensure valve outlet cap nut or plug (where provided) is correctly fitted.  
Open valve slowly to avoid pressure shock.  
Do not allow backflow into the container.  
Entering of water into the container must be prevented.  
No water to valves, flanges and other fittings.  
Purging of pipes and valves with inert gases - to avoid: water, solvents.

**Advices on general occupational hygiene**

When using do not eat, drink, smoke, sniff.  
Wash hands before breaks and after work.  
Remove contaminated clothing and protective equipment before entering eating areas.

**Mixture 90 % Ethylene oxide / 10 % Carbon dioxide**

Print date 08.07.2025  
 Revision date 08.07.2025  
 Version 16.0 (en)  
 replaces version of 21.12.2022 (15.0)

**7.2 Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

All regulations and local requirements for the storage of containers have to be respected.  
 Keep container tightly closed and in a well-ventilated place.  
 Containers' temperature should not be increased above 50 °C.  
 Prevent cylinders from falling over.  
 Only use containers specifically approved for the substance/product.  
 Information on suitable materials for receptacles and valves see ISO 11114.

**Materials to avoid**

Do not store together with explosives.  
 Do not store together with flammable liquids.  
 Do not store together with flammable solids.  
 Do not store together with pyrophoric and self-heating substances.  
 Do not store together with oxidizing liquids or oxidizing solids.  
 Do not store together with toxic liquids or toxic solids.  
 Do not store together with infectious substances.  
 Do not store together with radioactive material.  
 Do not store together with food or feed.

**Further information on storage conditions**

Recommended storage temperature: ≤ 10 °C.

**\* 7.3 Specific end use(s)**

- \* Recommendation**  
 Sterilisation of medical devices, medicinal products and their (empty) packaging  
 An exposure scenario is not required.

**\* SECTION 8: Exposure controls/personal protection****\* 8.1 Control parameters****\* Occupational exposure limit values**

CAS No	EC No	Substance name	occupational exposure limit value
124-38-9	204-696-9	Carbon dioxide	5000 [ml/m <sup>3</sup> (ppm)] 9000 [mg/m <sup>3</sup> ] Short-term(ml/m <sup>3</sup> ) 15000 (1) Short-term(mg/m <sup>3</sup> ) 27000 (1) (1) 15 minutes reference period (IE)
75-21-8	200-849-9	Ethylene oxide	1 [ml/m <sup>3</sup> (ppm)] 1.8 [mg/m <sup>3</sup> ] (IE)

**\* DNEL worker**

CAS No	Substance name	DNEL value	DNEL type	Remark
75-21-8	ethylene oxide	10 mg/m <sup>3</sup>	acute inhalative (systemic)	Assessment factor 10
75-21-8	ethylene oxide	1.8 mg/m <sup>3</sup>	long-term inhalative (local)	
75-21-8	ethylene oxide	1.8 mg/m <sup>3</sup>	long-term inhalative (systemic)	

**\* PNEC**

CAS No	Substance name	PNEC Value	PNEC type	Remark
75-21-8	ethylene oxide	0.084 mg/L	aquatic, freshwater	
75-21-8	ethylene oxide	0.84 mg/L	aquatic, intermittent release	
75-21-8	ethylene oxide	0.0084 mg/L	aquatic, marine water	
75-21-8	ethylene oxide	0.329 mg/kg	sediment, freshwater	
75-21-8	ethylene oxide	0.0329 mg/kg	sediment, marine water	
75-21-8	ethylene oxide	13 mg/L	sewage treatment plant (STP)	
75-21-8	ethylene oxide	0.0165 mg/kg	soil	

**Mixture 90 % Ethylene oxide / 10 % Carbon dioxide**

Print date 08.07.2025  
 Revision date 08.07.2025  
 Version 16.0 (en)  
 replaces version of 21.12.2022 (15.0)

**8.2 Exposure controls****Appropriate engineering controls****Technical measures to prevent exposure**

Transfer and handle only in enclosed systems.

**Personal protection equipment****Eye/face protection**

Protective goggles according to EN 166, in case of increased risk add protective face shield.

**Hand protection**

Safety gloves according to EN 374:

Glove material specification [make/type, thickness, permeation time/life]: IIR,  $\geq 0,7$  mm,  $> 30$  min

**Body protection:**

Safety shoes with steel toecap.

Body covering work clothing or chemical resistant suit at increased risk.

**Respiratory protection**

Keep self contained breathing apparatus readily available for emergency use.

Respiratory protection necessary at:

high concentrations

Suitable respiratory protection apparatus:

Respiratory protection complying with EN 137.

Short term: filter apparatus, filter AX

In case of rescue and maintenance activities in storage containers use environment-independent breathing apparatus because of risk of suffocation due to displacement of oxygen.

**Thermal hazards**

Use cold-resistant protective equipment.

**Environmental exposure controls****Remark**

Prevent release to the environment.

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties****Physical state**

Gaseous / liquefied under pressure.

**Colour**

colourless

**Odour**

like:

Ether

**Safety relevant basis data**

	Value	Method	Source, Remark
Odour threshold:			not determined
Melting point/freezing point			not applicable
Boiling point or initial boiling point and boiling range	10.5 °C		Information concerns ethylene oxide.
flammability			flammable
Lower and upper explosion limit	Upper explosion limit 100 Vol-%		Information concerns ethylene oxide.
Lower and upper explosion limit	Lower explosion limit 2.6 Vol-%		Information concerns ethylene oxide.
Flash point			not applicable
Auto-ignition temperature	429 °C		Information refers to ethylene oxide.

**Mixture 90 % Ethylene oxide / 10 % Carbon dioxide**

Print date 08.07.2025  
 Revision date 08.07.2025  
 Version 16.0 (en)  
 replaces version of 21.12.2022 (15.0)

	Value	Method	Source, Remark
Decomposition temperature	approx. 570 °C		Information refers to ethylene oxide.
pH			not applicable
Viscosity			not applicable
Solubility(ies)	Water solubility		not determined
Partition coefficient n-octanol/water (log value)			not applicable
Vapour pressure	7050 hPa (20°C)		calculated
Density and/or relative density			not applicable
Relative vapour density	1.56 (20°C) pressure 1013 hPa		air = 1 Information refers to ethylene oxide.
particle characteristics			not applicable

**9.2 Other information****Other information**

Vapours are heavier than air.

**\* SECTION 10: Stability and reactivity****\* 10.1 Reactivity**

Formation of explosive gas mixtures in contact with air.

**10.2 Chemical stability**

Hydrolyses

**10.3 Possibility of hazardous reactions**

Risk of polymerisation.  
 Reactions with numerous chemical compounds.  
 Reactions with light metals.  
 Reactions with alkali metals.  
 Reactions with amines.

**10.4 Conditions to avoid**

Water / moisture.  
 Light  
 Heat sources / heat - risk of bursting.  
 Ignition sources, open flames, glowing metal surfaces, etc.

**10.5 Incompatible materials**

Air  
 copper  
 Oxidising agent  
 Alcohols  
 Chlorine

**10.6 Hazardous decomposition products**

When handled and stored appropriately, no dangerous decomposition products are known.



**Mixture 90 % Ethylene oxide / 10 % Carbon dioxide**

Print date 08.07.2025  
 Revision date 08.07.2025  
 Version 16.0 (en)  
 replaces version of 21.12.2022 (15.0)

**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity****Animal data**

	Effective dose	Method, Evaluation	Source, Remark
Acute oral toxicity	CAS No75-21-8 ethylene oxide LD50: 330 mg/kg Species Rat	OECD 401	
Acute dermal toxicity			Study scientifically not necessary.
Acute inhalation toxicity	CAS No75-21-8 ethylene oxide LC50: 660 ppm Species Mouse Exposure time 4 h	OECD 403	

**Assessment/classification**

Toxic by inhalation and if swallowed.

**Skin corrosion/irritation****Animal data**

Result / Evaluation	Method	Source, Remark
corrosive Species Rabbit		Information concerns ethylene oxide.

**Assessment/classification**

Causes severe burns.

**Serious eye damage/irritation****Animal data**

Result / Evaluation	Method	Source, Remark
Corrosive Species Rabbit		Information concerns ethylene oxide.

**Assessment/classification**

Causes serious eye damage.

**Sensitisation to the respiratory tract****Other information**

No data available

**Skin sensitisation****Animal data**

Result / Evaluation	Dose / Concentration	Method	Source, Remark
not sensitising.	Species Guinea pig		Information concerns ethylene oxide.

**Assessment/classification**

Based on available data, the classification criteria are not met.

**Germ cell mutagenicity**

	Value	Method	Result / Evaluation	Remark
In vitro mutagenicity/genotoxicity			positive	Information concerns ethylene oxide.
In vivo mutagenicity/genotoxicity			positive	Information refers to ethylene oxide.

**Mixture 90 % Ethylene oxide / 10 % Carbon dioxide**

Print date 08.07.2025  
 Revision date 08.07.2025  
 Version 16.0 (en)  
 replaces version of 21.12.2022 (15.0)

**Assessment/classification**

May cause genetic defects.

**Carcinogenicity****Animal data**

	Value	Method	Result / Evaluation	Remark
Carcinogenicity	NOAEC < 10 ppm Species Rat Exposure duration 2 a	OECD 453		Information concerns ethylene oxide.

**Assessment/classification**

May cause cancer by inhalation.

**Reproductive toxicity****Animal data**

	Value	Method	Result / Evaluation	Remark
Reproductive toxicity	NOAEC 33 ppm	OECD 415		Information concerns ethylene oxide.

**Assessment/classification**

May damage fertility. Suspected of damaging the unborn child.

**STOT-single exposure****STOT SE 3****Irritation to respiratory tract****Assessment/classification**

May cause respiratory irritation.

**Narcotic effects****Assessment/classification**

May cause drowsiness or dizziness.

**STOT-repeated exposure****Animal data**

	Effective dose	Method	Specific effects:	Organs affected:	Source, Remark
Inhalative specific target organ toxicity (repeated exposure)	450 ppm Species Rat	OECD 413		haematopoietic system	Information concerns ethylene oxide.
Inhalative specific target organ toxicity (repeated exposure)	450 ppm Species Rat	OECD 413		central nervous system	Information concerns ethylene oxide.

**Assessment/classification**

Causes damage to the nervous system and to blood forming organs through prolonged or repeated exposure by inhalation.

**Aspiration hazard****Assessment/classification**

Study technically not feasible.

**11.2 Information on other hazards****Other information**

May be absorbed through the skin.

Risk of strong health injuries in case of long-term exposition.

The product has not been tested. The information is derived from the properties of the individual components.

**Mixture 90 % Ethylene oxide / 10 % Carbon dioxide**

Print date 08.07.2025  
 Revision date 08.07.2025  
 Version 16.0 (en)  
 replaces version of 21.12.2022 (15.0)

**\* SECTION 12: Ecological information****\* 12.1 Toxicity****\* Aquatic toxicity**

	Effective dose	Method, Evaluation	Source, Remark
Acute (short-term) fish toxicity	LC50: 52 mg/L Species <i>Oncorhynchus mykiss</i> (Rainbow trout) Test duration 96 h	EPA 660/3-75/009	Analogous to a similar product.
Chronic (long-term) fish toxicity	not determined		
Acute (short-term) toxicity to crustacea	EC50 212 mg/L Species <i>Daphnia magna</i> (Big water flea) Test duration 48 h	EPA 660/3-75/009	Information concerns ethylene oxide.
Chronic (long-term) toxicity to aquatic invertebrate	not determined		
Acute (short-term) toxicity to algae and cyanobacteria	EC50 240 mg/L Species <i>Raphidocelis subcapitata</i> Test duration 96 h	EPA 660/3-75/009	Analogous to a similar product.
Chronic (long-term) toxicity to aquatic algae and cyanobacteria	not determined		
Toxicity to other aquatic plants/organisms	not determined		
Toxicity to microorganisms	EC10 130 mg/L Species activated sludge Test duration 3 h	OECD 209	Information concerns ethylene oxide.

**12.2 Persistence and degradability**

	Value	Method	Source, Remark
Biodegradation	Degradation rate > 83 % Test duration 14 d		CAS No75-21-8 ethylene oxide

**Assessment/classification**

Readily biodegradable (according to OECD criteria).

**12.3 Bioaccumulative potential****Assessment/classification**

No data available

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

The substance/mixture does not contain components meeting the PBT/vPvB criteria of the Reach Regulation, Annex XIII, at levels of 0.1% or higher.

**\* 12.6 Endocrine disrupting properties**

No data available

**12.7 Other adverse effects****Additional ecotoxicological information****Additional information**

The product has not been tested. The data are derived from the individual components of the mixture.

**Mixture 90 % Ethylene oxide / 10 % Carbon dioxide**

Print date 08.07.2025  
 Revision date 08.07.2025  
 Version 16.0 (en)  
 replaces version of 21.12.2022 (15.0)

**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Waste codes/waste designations according to EWC/AVV**

Waste code product	Waste name
160504 *	gases in pressure containers (including halons) containing hazardous substances

**Appropriate disposal / Product**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.  
 Prevent release to the environment. No disposal via the sewage.

**Appropriate disposal / Package**

Transportable pressure equipment (empty, residual pressure): Return to supplier / manufacturer.

**SECTION 14: Transport information**

	Land transport (ADR/RID)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
<b>14.1 UN number or ID number</b>	UN 3300	UN 3300	UN 3300
<b>14.2 UN proper shipping name</b>	ETHYLENE OXIDE AND CARBON DIOXIDE MIXTURE	ETHYLENE OXIDE AND CARBON DIOXIDE MIXTURE	Ethylene oxide and carbon dioxide mixture
<b>14.3 Transport hazard class(es)</b>	2.3 (2.1)	2.3 (2.1)	2.3 (2.1)
<b>14.4 Packing group</b>	-	-	-
<b>14.5 Environmental hazards</b>	No	No	No

**14.6 Special precautions for user**

The protective measures listed in Sections 6, 7 and 8 of the Safety Data Sheet have to be considered.

**14.7 Maritime transport in bulk according to IMO instruments**

No carriage in bulk.

**Land transport (ADR/RID)**

UN number or ID number	UN 3300
UN proper shipping name	ETHYLENE OXIDE AND CARBON DIOXIDE MIXTURE
Transport hazard class(es)	2.3 (2.1)
Hazard label(s)	2.3+2.1
Classification code	2TF
Packing group	-
Environmental hazards	No
Limited quantity (LQ)	0
Special provisions	-
Tunnel restriction code	B/D

**Sea transport (IMDG)**

UN number or ID number	UN 3300
UN proper shipping name	ETHYLENE OXIDE AND CARBON DIOXIDE MIXTURE
Transport hazard class(es)	2.3 (2.1)
Packing group	-
Environmental hazards	No
Limited quantity (LQ)	0
Marine pollutant	No

**Mixture 90 % Ethylene oxide / 10 % Carbon dioxide**

Print date 08.07.2025  
 Revision date 08.07.2025  
 Version 16.0 (en)  
 replaces version of 21.12.2022 (15.0)

EmS F-D, S-U

**Air transport (ICAO-TI / IATA-DGR)**

UN number or ID number UN 3300  
 UN proper shipping name Ethylene oxide and carbon dioxide mixture  
 Transport hazard class(es) 2.3 (2.1)  
 Packing group -  
 Environmental hazards No

**Remark**  
 FORBIDDEN

**\* SECTION 15: Regulatory information**

**\* 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**\* EU legislation**

**Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.  
 Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

**\* Other regulations (EU)**

**To follow:**  
 Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), Annex XVII No 28 - 30.  
 Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), Annex XVII No 40.  
 Regulation (EU) 2017/745 on medical devices.  
 Regulation (EU) 2019/6 on veterinary medicinal products.  
 Directive 2001/83/EC on the Community code relating to medicinal products for human use.  
 Regulation (EU) No 649/2012 concerning the export and import of dangerous chemicals.  
 Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances.  
 - 20. Ethylene oxide  
 National and local regulations concerning chemicals shall be observed.

**Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive] VOC**

VOC-value 90 %

**15.2 Chemical Safety Assessment**

**National regulations**

Chemical safety assessments for substances in this mixture were carried out.

**SECTION 16: Other information**

**Abbreviations and acronyms**

Press. Gas (Liq.): Liquefied gas (LG)  
 Acute Tox. 3, H301: Acute Toxicity (oral), Category 3  
 Skin Corr. 1: Skin corrosion, Category 1  
 Eye Dam. 1: Serious eye damage, Category 1  
 Muta. 1B: Germ cell mutagen, Sub-category 1B  
 Carc. 1B: Carcinogen, Category 1B  
 Repr. 1B: Reproductive toxicant, Category 1B  
 STOT SE 3, H335: Specific target organ toxicity (single exposure), Category 3  
 STOT SE 3, H336: Specific target organ toxicity (single exposure), Category 3 (narcotic effects)  
 STOT RE 1: Specific target organ toxicity (repeated exposure), Category 1  
 Acute Tox. 3, H331: Acute Toxicity (inhalation), Category 3  
 Chem. Unst. Gas A: Chemically unstable gas, Category A

**Key literature references and sources for data**

Information from our suppliers and data from the "GESTIS Substances Database" and the "Registered Substances" database of the European Chemicals Agency (ECHA) were used to create this safety data sheet.

**Mixture 90 % Ethylene oxide / 10 % Carbon dioxide**

Print date 08.07.2025  
Revision date 08.07.2025  
Version 16.0 (en)  
replaces version of 21.12.2022 (15.0)

**Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]**

Classification of the mixture based on bridging principles (physical hazards) and specific and general concentration limits of the ingredients (health and environmental hazards).

**Additional information**

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

**Relevant H- and EUH-phrases (Number and full text)**

H220 H230	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.
H301	Toxic if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350i	May cause cancer by inhalation.
H360Fd	May damage fertility. Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.

**Indication of changes**

\* Data changed compared with the previous version